



- WBS approved insulation board thickness to suit client requirements
- WBS alkali resistant glass fibre scrim bedded in WBS scrim adhesive 4-6mm
- Levelling coat of WBS scrim adhesive 2-3mm
- WBS cavity spacer track screw fixed into SIPS panel
- WBS silicone primer coat (colour to clients approval)
- WBS silicone finish coat (grain size and colour to clients approval)
- SIPS panel by others
- 15mm drainage cavity behind the insulation boards
- WBS approved self tapping insulation board fixing fixed into WBS cavity spacer track
- WBS Stainless steel drainage deflector bead bedded on silicone sealant and mechanically fixed at 300mm centres to SIPS panel. Bead to be fitted above window and door openings fixed at min 10 degree slope.
- WBS PVC Corner bead bedded in scrim adhesive
- WBS expanding foam filler
- WBS APU frame seal or silicone sealant
- Conjectured line of window

drawing. **Window head detail**

date. July 2009

scale. nts

drawing no. **SIPS-EPSITEC-EWI-05**

revision. -

Wetherby Building Systems Ltd

1 Kid Glove Road, Golborne Enterprise Park,  
 Golborne, Greater Manchester, WA3 3GS  
 Tel: 01942 717100 Fax: 01942 717101  
 Web: [www.wbs-ltd.co.uk](http://www.wbs-ltd.co.uk)  
 E-mail: [technical@wbs-ltd.co.uk](mailto:technical@wbs-ltd.co.uk)