



Kooltherm®

PRODUCT SAFETY INFORMATION

These products are exempt from the requirements of Article 57 and 59(1) of REACH Regulation (EC) No 1907/2006. The information below follows the SDS format as described in Annex 2 of the Regulation.

1 Identification of Products and Company

Products

Kingspan Kooltherm® K103 Floorboard
 Kingspan Kooltherm® K106 Cavity Board
 Kingspan Kooltherm® K107 Pitched Roof Board
 Kingspan Kooltherm® K108 Cavity Board
 Kingspan Kooltherm® K110 Soffit Board
 Kingspan Kooltherm® K110 PLUS Soffit Board
 Kingspan Kooltherm® K112 Framing Board
 Kingspan Kooltherm® K118 Insulated Plasterboard
 Kingspan Kooltherm® K5 External Wall Board
 Kingspan Kooltherm® K7 Pitched Roof Board
 Kingspan Kooltherm® K8 Cavity Board
 Kingspan Kooltherm® K9
 Kingspan Kooltherm® K10 FM Soffit Board
 Kingspan Kooltherm® K10 PLUS Soffit Board
 Kingspan Kooltherm® K12 Framing Board
 Kingspan Kooltherm® K15 Rainscreen Board
 Kingspan Kooltherm® K17 Insulated Plasterboard
 Kingspan Kooltherm® K18 Insulated Plasterboard
 Kingspan Kooltherm® Cavity Closer
 Kingspan Kooltherm® Duct Insulation
 Kingspan KoolDuct®

Company

Kingspan Insulation Limited
 Pembridge
 Leominster
 Herefordshire, HR6 9LA, UK
 Tel: +44 (0) 1544 388 601
 Fax: +44 (0) 1544 388 888
 Email: info@kingspaninsulation.co.uk
 Website: www.kingspaninsulation.co.uk



2 Hazards Identification

Not applicable.

3 Composition

Core: Rigid thermoset phenolic (as defined in EN13166) insulation.

Alternative Facings: Reinforced foil complex (K106, K110, K118, K10, K15, K17, K18, Duct Insulation).
Composite foil (K107, K108, K112, K7, K8, K12).

DISCLAIMER Recipients of WBS products must take responsibility for existing laws and regulations and at all times operate within the Health and Safety guidance on the use of these products.

This is a direct copy of the manufacturers Safety Data Sheet, and Wetherby Building Systems Ltd takes no responsibility for the contents.

Glass tissue (K103, K110, K110 PLUS, K118, K3, K5, K9, K10, K10 PLUS, K17, K18, Duct Insulation).
Non-combustible building board (K110 PLUS, K10 PLUS)
Polypropylene fleece (K106)
Plasterboard (K118, K17, K18).
PVC (Cavity Closer).

4 First-Aid Measures

- Inhalation:** Dust is non-hazardous.
Remove the person to fresh air.
- Skin:** Non-sensitising.
When facings containing glass fibres are handled, skin irritation may occur. Wash carefully using soap and water or a proprietary cleanser to remove.
- Eyes:** Dust particles should be removed by flushing with clean water.
- Ingestion:** No information available.
- Other:** Seek medical attention if discomfort persists.

5 Fire-Fighting Measures

It is prudent to take precautions against ignition, fire spread and smoke hazard.

Suitable media: Waterspray (fog), foam, CO₂ or dry chemical.

Un-suitable media: Not applicable.

Fire fighters should use self contained breathing apparatus and saturate burning foam with water from a spray nozzle. Dust is classified as weakly explosive (St. Class 1).

6 Accidental Release Measures

Not applicable.

7 Handling and Storage

Store in original packing in a location free from any ignition hazard such as open flames, cutting and welding torches, high surface temperature electric heaters and other forms of direct radiant heat.

Keep product protected from the elements. Ensure stability of stack and provide adequate aisle space for access between stacks.

8 Exposure Controls / Personal Protection

- Inhalation:** Dust is non-hazardous.
As with all cutting procedures it is recommended that a disposable dust mask be worn.
Where dust is generated through mechanical cutting in confined spaces, it is recommended that extraction be used.
- Hands:** It is recommended that gloves be worn when handling the products.
- Eyes:** Eye protection recommended during mechanical cutting.
When installing a product with reflective foil facings in very bright or sunny weather it is advisable to wear UV protective sunglasses or goggles.
- Skin:** Non-sensitising.
It is recommended to wear gloves when handling the products.
When installing a product with reflective facings in bright sunlight, it is advisable to consider skin protection from UV.
- Other:** The products are non-load bearing.
Access and work should not be carried out on un-supported boards.
The smooth facing used on some Kooltherm products can be slippery underfoot when wet.

9 Physical and Chemical Properties

- Appearance:** Peach / yellow / brown foam with reinforced foil complex, composite foil, bitumen coated perlite, glass tissue, plasterboard or PVC facings.

Odour:	Negligible.
pH:	Neutral under normal conditions.
Melting point:	Not applicable.
Flash point:	Not applicable.
Insulation density:	Typically 30-60 kg/m ³ .
Solubility in water:	Insoluble.
Solubility in organics:	Some liquids might cause swelling.
Other data:	None.

10 Stability and Reactivity

Stable and un-reactive during normal use (see section 7).

11 Toxicological Information

No information available at this time.

12 Ecological Information

The products are inert and stable in water and soil.

13 Disposal Considerations

Waste insulation is non-hazardous.

Product dust created in the installation process is regarded as nuisance dust only, because of its inert nature.

Observe usual safety precautions with polythene bags, wrapping and packaging.

Clean, undamaged product may be re-used. Insulation core waste is fully recyclable.

Waste product should be disposed of in accordance with the Waste Hierarchy – Reduce, Re-Use, Recycle.

14 Transport Information

Read this section in conjunction with section 7.

Ensure security of load and where necessary sheeting / roping should be used.

It is recommended that mechanical lifting equipment is used when moving bulk quantities.

15 Regulatory Information

Not applicable.

16 Other Information

The information contained here is offered in good faith and is based on our current knowledge. We thereby withhold the right to update and amend this document as necessary.

The information should not be taken as guarantee of specific performance and users should make their own assessment and make all applicable personnel aware accordingly.

The wearing of appropriate safety equipment is strongly recommended as a precaution and the product should only be used in its design application.

Users should visit the Kingspan Insulation website or contact the Kingspan Insulation Technical Service Department to ensure information is current.



Kingspan Insulation Ltd

Pembridge, Leominster, Herefordshire HR6 9LA, UK
Tel: +44 (0) 1544 388 601 Fax: +44 (0) 1544 388 888
email: info@kingspaninsulation.co.uk

www.kingspaninsulation.co.uk